## **TECHNICAL DATA SHEET**



Code Nr	5110 AC V FFP1 NR D	
Product Name	ERA	
Series	A.Carbon Vertical Folding Series	
Aplication Limit	4 x OEL protection level (Acording to Npf)	
Places of use	Building, Ship building, Pharmaceutical industry, Engineering,Iron and steel, Agriculture, Coal mining, etc.	
Description	The disposable flat fold respirator consists of several layers of material.	
Working principle	Particles are filtered through the melt blown filter.	
Weight	12 gr	

# Particulate Respirators

#### **Components and materials**

The following materials are used in the production of the FFP1

Component	Material
Filter material	Polypropylene
Head Straps	Knit Rubber
Valve	Polypropylene
Nose clip	Aluminium

#### **Maximum Filter Penetration**

EN149:2001+A1:2009	Maximum Filter		
Classification	Penetration		
FFP1	20%		

#### **Total inward leakege**

EN149:2001+A1:2009	Maximum Total Inward				
Classification	Leakage				
FFP1	22%				

#### **Breathing resistance**

EN 149:2001+A1:2009	Maximum Breathing Resistance			
Classification	Inhalation at 30I/min		Exhalation at 160I/min	
FFP1	0.6 mbar	2.1 mbar	3.0 mbar	

### Clogging

For single shift use respirators (NR), the clogging test is optional. For re-usable respirators this test is mandatory. The respirators are loaded with very high amount of Dolomite dust which will tend to clog the filter. After loading with the required amount of dust, the breathing resistance of the respirators shall not exceed the following limits

EN 149:2001+A1:2009 Classification	Maximum Breathing Resistance Inhalation at 951/ Exhalation at min 1601/ min		
FFP1	<ul><li>4.0 mbar (val- ved respirator)</li><li>3.0 mbar (unvalved respirator)</li></ul>	3.0 mbar (valved respirator)	

#### **Ordering Information**

Descirption	Barcode	Packing Steel	Pcs In Box	Pcs In Carton	Gross Box	Size of Box
5110 AC V FFP1 NR D	8681248449435	Individual	15	270	6.8 kg	72x52x27 cm



Phone: +90 216 394 47 59 pbx

E-mail : export@eratozmaskesi.com - export@eramaske.com web : www.eratozmaskesi.com - www.eramaske.com