TECHNICAL DATA SHEET





Code Nr	6300 FFP3 NR D		
Product Name	ERA		
Series	Conical Professional Series		
Aplication Limit	50 x OEL protection level (Acording to Npf)		
Places of use	Building, Ship building,Pharma- ceutical industry, Engineering,Iron and steel, Agriculture, Coal mining, etc.Medical, Hospital, Droplet aeresols,Protein molecules, Virus- ses, Bacteria fungi and spores, Asbestos fibers		
Description	The disposable flat fold respirator consists of several layers of material.		
Working principle	Particles are filtered through the melt blown filter.		
Weight	12 gr		

Components and materials

The following materials are used in the production of the FFP3

Component	Material		
Filter material	Polypropylene		
Head Straps	Knit Rubber		
Nose clip	Aluminum (Optional)		

Maximum Filter Penetration

EN149:2001+A1:2009	Maximum Filter
Classification	Penetration
FFP3	1%

Total inward leakege

EN149:2001+A1:2009 Classification	Maximum Total Inward Leakage		
FFP3	2%		

Breathing resistance

	EN 149:2001+A1:2009	Max	cimum Breat Resistance	
1	Classification	Inhalation at 30I/min		Exhalation at 160l/min
	FFP3	1 0 mhar	3 mhar	3.0 mhar

Clogging

For single shift use respirators (NR), the clogging test is optional. For re-usable respirators this test is mandatory. The respirators are loaded with very high amount of Dolomite dust which will tend to clog the filter. After loading with the required amount of dust, the breathing resistance of the respirators shall not exceed the following limits

EN 149:2001+A1:2009 Classification	Maximum Brea Resistance Inhalation at 95I/ min	
FFP3	7.0 mbar (valved respirator)	3.0 mbar (valved respirator)

Ordering Information						
Descirption Barcode Packing Steel Pcs In Box Pcs In Carton Gross Box Size of					Size of Box	
6300 FFP NR D	8681248449466	Multiple	10	120	4.25 kg	44x45.5x45 cm

Marking

NR: Non Reusable (single shift use only)

: (Dolomite) Meets the clogging resistance requirements



End of Shelf Life.
Date format: YYYY/MM/DD

Maximum Relative Humidity



Tempature Range



Name and address of Legal Manufacturer













Phone: +90 216 394 47 59 pbx E-mail: export@eratozmaskesi.com - export@eramaske.com web: www.eratozmaskesi.com - www.eramaske.com